



Go The Extra Yard.™



## MODEL: ComfortControl™ DD

SPECIFICATIONS: Dated 9-1-2011

<b>TYPE:</b>	Intermediate walk mower with dual drive hydrostatic type transmission	<b>TIRES:</b>	Drive - 18 x 7.5 (48"), 18 x 8.5 (52" & 61"), 4 ply Caster - 9 x 3.5, 4 ply, tube type with bolt together rims
<b>DECK SIZE:</b>	48", 52" & 61"	<b>FRONT CASTERS:</b>	1" shaft tapered roller bearings
<b>ENGINE:</b>	20.5 gross HP** Kawasaki FX651V or 23.5 gross HP** Kawasaki FX730V, electric start pressure lubrication and spin on oil filter	<b>DECK:</b>	10 gauge with lap-welded corners, plug welded double top deck, full spindle width and metal deck shields
<b>AIR CLEANER:</b>	Centrifugal, dry type w/replaceable element, two stage	<b>QUICK ADJUST DECK:</b>	1.75" to 4.75"
<b>FUEL CAPACITY:</b>	5 gallons with 3.5" cap.	<b>SPINDLES:</b>	Cast aluminum with 2.5" X 1" dual ball bearings, top access grease fittings with weep holes
<b>DRIVE SYSTEM:</b>	Twin, independent, Eaton unitized transaxles, with cooling fins and top mounted cooling fans, visual fluid level expansion chamber, no high-pressure external lines	<b>SPINDLE PULLEYS:</b>	Split steel.
<b>SPEED:</b>	0 - 6 MPH forward 0 - 3 MPH reverse	<b>BLADES:</b>	0.25" thick, heat-treated, Marbain
<b>CONTROL SYSTEM:</b>	Infinitely variable speeds, cruise control and maximum 3" travel on individual left/right turning and speed control handles; Foot activated neutral with independent steering override	<b>PAINT:</b>	Polyester powder coat paint; TGIC
<b>PARKING BRAKE:</b>	Dynamic thru transaxles	<b>WARRANTY:</b>	Two (2) year commercial warranty, parts and labor. (90 days on belts, blades, tires and brake pads) Kawasaki engine (3) year limited manufacturer's warranty
<b>BLADE ENGAGEMENT:</b>	Electric clutch.		
<b>DUMP VALVES:</b>	Twin independent, pull type with easy top access		

\*All power levels are stated gross horsepower per SAE J1940 as rated Briggs & Stratton. \*\*All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki. ^Power levels rated by engine manufacturer. Not all models available in California. Models subject to change.



Go The Extra Yard.™



## MODEL: ComfortControl™ DD 15/36

SPECIFICATIONS: Dated 9-1-2011

<b>TYPE:</b>	Intermediate walk mower with dual drive hydrostatic type transmission	<b>DECK:</b>	Torque Tuned Blade™ System, 10 gauge with lap-welded corners, plug welded double top deck, full spindle width and metal deck shields
<b>DECK SIZE:</b>	36" side discharge	<b>QUICK ADJUST DECK:</b>	1.5" to 4.5"
<b>ENGINE:</b>	15 gross HP** Kawasaki FS541V; pressure lubrication and spin on oil filter	<b>SPINDLES:</b>	Cast aluminum with 2.5" X 1" dual ball bearings, top access grease fittings with weep holes
<b>FUEL CAPACITY:</b>	5 gallons with 3.5" cap	<b>SPINDLE PULLEYS:</b>	Split steel
<b>DRIVE SYSTEM:</b>	Dual heavy-duty Hydro-Gear ZT-3100 hydraulic transmission; Self-contained, charge pump design, steel cut gears, 1" axle shaft, spin-on oil filter and steel oil filter guard	<b>BLADES:</b>	0.25" thick, heat-treated, Marbain
<b>CONTROL SYSTEM:</b>	Infinitely variable speeds, cruise control and maximum 3" travel on individual left/right turning and speed control handles. Foot activated neutral with independent steering override	<b>PAINT:</b>	Polyester powder coat paint; TGIC
<b>PARKING BRAKE:</b>	Internal transaxles	<b>WARRANTY:</b>	Two (2) year commercial warranty, parts and labor (90 days on belts, blades, tires and brake pads) Kawasaki engine (3) year limited manufacturer's warranty
<b>BLADE ENGAGEMENT:</b>	Electric clutch		
<b>DUMP VALVES:</b>	Twin independent, pull type with easy top access		
<b>TIRES:</b>	Drive - 18 x 6.5, 4 ply Caster - 9 x 3.5, 4 ply, Flat-free with bolt together rims		
<b>FRONT CASTERS:</b>	1" shaft tapered roller bearings		

\*All power levels are stated gross horsepower per SAE J1940 as rated Briggs & Stratton. \*\*All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki. ^Power levels rated by engine manufacturer. Not all models available in California. Models subject to change.