MODEL: HydroCut™

SPECIFICATIONS: Date 9-15-2012

TYPE:	Intermediate type walk mower with single hydrostatic drive
DECK SIZE:	32”, 36”
ENGINE:	15 gross HP** Kawasaki® FS541V, electric start, twin cylinder, pressure lubrication and spin on oil filter
FUEL CAPACITY:	5 gallons with 3.5” cap
DRIVE SYSTEM:	Hydrogear transaxle with cooling fins, fan, and expansion chamber, no high-pressure lines
SPEED:	0 - 5.5 MPH forward 0 - 2 MPH reverse
CONTROL SYSTEM:	Thumb controls for infinitely variable forward and reverse speeds
BLADE ENGAGEMENT:	Electric clutch
DUMP VALVE:	Lever type with easy side access
TIRES:	Drive: 16 x 6.5 x 8, 4 ply Caster: 9 x 3.5 x 4, 4 ply tube type with bolt together rims
DECK:	10 gauge with lap welded corners, spindle reinforcement plates and metal deck shield with easy access hold-downs; Torque Tuned Blade™ System (36”)
DRIVE SPINDLE PULLEY:	Split steel (32”)
BLADE SPINDLE PULLEYS:	Cogged sprockets (36”)
SPINDLES:	Cast aluminum with 2.5” X 1” dual ball bearings, top access grease fittings with weep holes
BLADES:	0.25 “ thick, heat treated, Marbain
PAINT:	Polyester powder coat paint. TGIC
WARRANTY:	**Walk Behind Mower**: 2 years (24 months) unlimited hours **Belts, Tires, Brake Pads, Hoses, Battery, Blades**: 90 days **Engine**: Kawasaki®: 3 Year Limited Manufacturer’s Warranty (36 month).

* All power levels are stated gross horsepower per SAE J1940 as rated Briggs & Stratton.
** All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.
^ Power levels rated by engine manufacturer.

Not all models available in California. Models subject to change.

5375 N Main Street • Munnsville, NY 13409 • 1-800-933-6175 • www.FerrisIndustries.com

1396_FER_FLY_0912