MODEL: EVOLUTION™

SPECIFICATIONS: Date 9-15-2012

FERRIS®

Go The Extra Yard.™

TYPE:	Compact mid mount, zero turn, twin stick steering rider with suspension
DECK SIZE:	36”, 48”, 52”
ENGINE:	19 gross HP** Kawasaki® FH580V, 20 gross HP** Kawasaki® FX600V, 26 gross HP** Kawasaki® FX730V or, 27 gross HP** Kawasaki® FX751V, pressure lubrication, spin on oil filter, remote air cleaner
SUSPENSION:	Patented Operator Forward Design and Ergonomics
FUEL TANKS:	5.2-gallons (36”); 8-gallons (48”, 52”). 3.5” cap. Integrated cup holder
DRIVE SYSTEM:	Twin independent wheel motors and pumps, fans on 61” model, five bolt wheel hubs, with 1/2 qt. spin on oil filter and reservoir mounted inside the frame
SPEED:	0 - 8 MPH forward (36”) 0 - 10 MPH forward (48” & 52”) 0 - 4 MPH reverse
CONTROL SYSTEM:	Adjustable steering
PARKING BRAKE:	Drum Style
BLADE ENGAGEMENT:	Electric clutch
HEIGHT CONTROL:	Foot activated, 0.25” increments, single pin adjust from 1.5” to 4.5”
TIRES:	Drive: 18 x 8.5 x 10 (36”) 20 x 10 x 10, 4 ply (48” & 52”) Caster: 11 X 4 x 5, 4 ply, Flat-free
DECK:	36”: Floating, 10 gauge with lap welded corners, plug welded second top deck, full spindle width and metal deck shields 48” & 52”: iCD™ Cutting System
DISCHARGE CHUTE:	Flexible rubber
BELTS:	Drive system - heavy-duty B-section belt to both pumps Deck drive - one continuous loop B-section belt for spindles and deck drive
SPINDLE PULLEYS:	Split Steel
SPINDLES:	Cast aluminum with 2.5” X 1” dual ball bearings, top access grease fittings with weep holes
BLADES:	0.25” thick, heat-treated, Marbain
FRAME:	1.5” by 2” 11-gauge rectangular tubing
HOUR METER:	Standard, activated with PTO
SEAT:	Adjustable, fore and aft
PAINT:	Polyester powder coat paint. TGIC
WARRANTY:	**Riding Mower**: 4 years (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months) **Belts, Tires, Brake Pads, Hoses, Battery, Blades**: 90 days **Engine**: Kawasaki®: 3 Year Limited Manufacturer’s Warranty (36 month).

* All power levels are stated gross horsepower per SAE J1940 as rated Briggs & Stratton.
** All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.
^ Power levels rated by engine manufacturer.

Not all models available in California. Models subject to change.