Go The Extra Yard.™

MODEL: EVOLUTION™

SPECIFICATIONS: Dated 9-1-2011

TYPE:	Compact mid mount, zero turn, twin stick steering rider with suspension
DECK SIZE:	36”, 48”, 52”
ENGINE:	27 HP (48") 26 HP (52") 20 HP (48") 19 HP (36") Kawasaki, pressure lubrication, spin on oil filter, remote air cleaner.
SUSPENSION:	Patent Pending Operator Forward Design and Ergonomics
FUEL TANKS:	Single, 5.2 gallon capacity 3.5” cap. Integrated cup holder
DRIVE SYSTEM:	Twin independent wheel motors and pumps, fans on 61” model, five bolt wheel hubs, with 1/2 qt. spin on oil filter and reservoir mounted inside the frame
SPEED:	0 - 10 MPH forward (52” / 48”) 0 - 8 MPH forward (36”) 0 - 4 MPH reverse
CONTROL SYSTEM:	Adjustable steering
PARKING BRAKE:	Drum Style
BLADE ENGAGEMENT:	Electric clutch
HEIGHT CONTROL:	Foot activated, 0.25" increments, single pin adjust from 1.5" to 4.5"
TIRES:	Drive: 18 x 8.5 x 10 (36”) 20 x 10 x 10, 4 ply (52” & 48”) Caster - 11 X 4 x 5, 4 ply, Flat-free
DECK:	52” & 48” : iCD™ Cutting System 36”: Floating, 10 gauge with lap welded corners, plug welded second top deck, full spindle width and metal deck shields
DISCHARGE CHUTE:	Flexible rubber
BELTS:	Drive system - heavy-duty B-section belt to both pumps Deck drive - one continuous loop B-section belt for spindles and deck drive
SPINDLE PULLEYS:	Split Steel
SPINDLES:	Cast aluminum with 2.5" X 1" dual ball bearings, top access grease fittings with weep holes
BLADES:	0.25" thick, heat-treated, Marbain
FRAME:	1.5" by 2" 11-gauge rectangular tubing
HOUR METER:	Standard, activated with PTO
SEAT:	Adjustable, fore and aft
PAINT:	Polyester powder coat paint. TGIC
WARRANTY:	Two (2) year commercial warranty, parts and labor. (90 days on belts, blades, tires and brake pads) Kawaski engine (3) year limited manufacturer's warranty