FERRIS®

Go The Extra Yard.™

MODEL: IS® 1500Z

SPECIFICATIONS: Dated 9-1-2011

TYPE:	Mid mount, zero turn, twin stick steering rider with suspension.
DECK SIZE:	44", 48", 52", 61"
ENGINE:	18.5 gross HP** Kawasaki FS600V, 24 gross HP** Kawasaki FS691V, 25 gross HP** Kawasaki FS730V, 26/28 gross HP* Briggs & Stratton Commercial Turf Series, pressure lubrication, spin on oil filter, remote air cleaner
AIR CLEANER:	Centrifugal, dry type w/replaceable element, two stage
SUSPENSION:	Four-wheel suspension with pivoting front axle, spring assemblies and rear-wheel coil-over-shock suspension.
FUEL TANKS:	Single, 5.5 gallon capacity 3.5" cap. Integrated cup holder
DRIVE SYSTEM:	Twin independent wheel motors and pumps with individual top mounted cooling 7" fans, 5 bolt wheel hubs, with 1/2 qt. spin on oil filter and reservoir mounted inside the frame
SPEED:	0 - 10 MPH forward 0 - 6 MPH reverse
CONTROL SYSTEM:	Twin fold over stick type, adjustable steering
PARKING BRAKE:	Drum Style
BLADE ENGAGEMENT:	Electric clutch
HEIGHT CONTROL:	Foot activated, 0.25" increments, single pin adjust from 1.75" to 5"
TIRES:	Drive: 22 x 11 x 10, 4 ply (52" & 61") 22 x 10 x 10, 4 ply (44" & 48") Caster - 13 x 5 x 6, 4 ply, tubeless, pneumatic
DECK:	48", 52" & 61": iCD™ Cutting System 44": Floating, 10 gauge with lap welded corners, plug welded second top deck, full spindle width and metal deck shields
DISCHARGE CHUTE:	Flexible rubber
BELTS:	Drive system - heavy-duty banded A-section belts to both pumps Deck drive - one continuous loop B-section belt for spindles and deck drive
SPINDLE PULLEYS:	Split Steel
SPINDLES:	Cast Aluminum with 2.5" x 1" dual ball bearings, top access grease fittings with weep holes
BLADES:	0.25" thick, heat-treated, Marbain
FRAME:	1.5" by 2" 11-gauge rectangular tubing
HOUR METER:	Standard, activated with PTO
SEAT:	Adjustable, fore and aft, with fold down arm rests
PAINT:	Polyester powder coat paint; TGIC
WARRANTY:	Two (2) year commercial warranty, parts and labor; (90 days on belts, blades, tires and brake pads) Kawasaki engine (3) year limited manufacturer's warranty Briggs engine (2) year limited manufacturer's warranty
ROPS:	Standard, folding roll-over protection with retractable seatbelt

*All power levels are stated gross horsepower per SAE J1940 as rated Briggs & Stratton. **All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki. ^Power levels rated by engine manufacturer. Not all models available in California. Models subject to change.

5375 N Main Street • Munnsville, NY 13409 • 1-800-933-6175 • www.FerrisIndustries.com