MODEL: IS® 2000Z

SPECIFICATIONS: Date 9-15-2012

FERRIS®

Go The Extra Yard.™

TYPE:	Mid mount, zero turn, twin stick steering rider with four-wheel suspension
DECK SIZE:	52”, 61”
ENGINE:	25.5 gross HP** Kawasaki® FX801V, 29 gross HP^ Kohler® EVC749 Command PRO EFI, 28/30 gross HP* Briggs & Stratton Commercial Turf Series™, 32 gross HP* Vanguard™ BIG BLOCK™, pressure lubrication, spin on oil filter, remote air cleaner
AIR CLEANER:	Centrifugal, dry type w/replaceable element, two stage (excludes Briggs & Stratton Commercial Turf Series™ engines)
SUSPENSION:	Front - independent with coil over, adjustable shocks Rear - coil-over shocks
FUEL TANKS:	Twin, selectable, 5.5 gallon capacity (total 11 gallons) with individual fuel gauges; Outboard mounted; 3.5” cap.; Integrated cup holder
DRIVE SYSTEM:	Twin independent wheel motors and pumps with individual top mounted 8” cooling fans, 5 bolt wheel hubs, 1/2 qt. spin on oil filter and reservoir and all hoses inside main frame
DRIVE AXLES:	1.25” tapered shaft
CONTROL SYSTEM:	Twin fold over stick type steering
SPEED:	0 - 10 MPH forward 0 - 6 MPH reverse
PARKING BRAKE:	Hand activated, drum
BLADE ENGAGEMENT:	Electric clutch
HEIGHT CONTROL:	Foot activated, 0.25” increments, single pin adjust from 1.75” to 5”
TIRES:	Drive: 22 x 10 x 10, 4 ply - (52”) 22 x 11 x 10, 4 ply - (61”) Caster: 13 x 5 x 6, 4 ply, tubeless, pneumatic
DECK:	iCD™ Cutting System
DISCHARGE CHUTE:	Flexible rubber
BELTS:	Drive system - heavy-duty banded A-section belt to each pump Deck drive - one continuous loop B-section belt for spindles and deck drive
SPINDLE PULLEYS:	Split steel
SPINDLES:	Cast-iron roller bearing spindles - 1” shaft has an 8” 6-bolt flange design; Greasable (61”)/Cast aluminum with 2.5” x 1” dual ball bearings, top access grease fittings with weep holes (52”)
BLADES:	0.25” thick, heat-treated, Marbain
FRAME:	1.5” by 2” 11-gauge rectangular tubing
DECK MOUNTING:	All four corners to be suspension mounted
HOUR METER:	Standard, activates with PTO
SEAT:	Premium adjustable seat with optional seat insert
PAINT:	Polyester powder coat paint; TGIC
WARRANTY:	**Riding Mower**: 4 years (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months) **Belts, Tires, Brake Pads, Hoses, Battery, Blades**: 90 days **Engine**: Briggs & Stratton Commercial Turf Series: 3 Year Limited Manufacturer’s Warranty (36 month). Vanguard™ BIG BLOCK™: 3 Year Limited Manufacturer’s Warranty (36 month). Kawasaki®: 3 Year Limited Manufacturer’s Warranty (36 month). Other: See Manufacturer’s Warranty
ROPS:	Standard, folding roll-over protection with retractable seatbelt

* All power levels are stated gross horsepower per SAE J1940 as rated Briggs & Stratton.
** All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.
^ Power levels rated by engine manufacturer.

Not all models available in California. Models subject to change.

5375 N Main Street • Munnsville, NY 13409 • 1-800-933-6175 • www.FerrisIndustries.com

1396_FER_FLY_0912