

MODEL: IS[®] 2500Z

SPECIFICATIONS: Date 9-15-2012



Go The Extra Yard.™



TYPE: Mid mount, zero turn, twin stick steering rider with four-wheel suspension

DECK SIZE: 52", 61"

ENGINE: 20 & 24 gross HP[^] Yanmar™ Diesel engine, pressure lubrication, spin on oil filter, remote air cleaner

AIR CLEANER: Centrifugal, dry type w/replaceable element, two stage

GAUGES & ALARMS: Water and oil pressure to be visual; Disengages PTO @ overheat stage; Fuel level gauge in each tank

SUSPENSION: Front - independent with coil over, adjustable shocks.
Rear - coil-over shocks

FUEL TANKS: Twin, selectable, 5.5 gallon capacity (total 11 gallons) with individual fuel gauges. Outboard mounted; 3.5" cap. Integrated cup holder

DRIVE SYSTEM: Twin independent wheel motors and pumps with individual top mounted 7" cooling fans, 5 bolt wheel hubs, 1/2 qt. spin on oil filter and reservoir and all hoses inside main frame

DRIVE AXLES: 1.25" tapered shaft

CONTROL SYSTEM: Twin fold over stick type steering

SPEED: 0 - 10 MPH forward
0 - 6 MPH reverse

PARKING BRAKE: Hand activated, drum

BLADE ENGAGEMENT: Electric clutch

HEIGHT CONTROL: Foot activated, 0.25" increments, single pin adjust from 1.75" to 5"

TIRES: Drive:
22 x 10 x 10, 4 ply - (52")
22 x 11 x 10, 4 ply - (61")
Caster:
13 x 5 x 6, 4 ply, tubeless, pneumatic

DECK: iCD™ Cutting System

DISCHARGE CHUTE: Flexible rubber

BELTS: Drive system - heavy-duty serpentine belt to each pump
Deck drive - one continuous loop B-section belt for spindles and deck drive

SPINDLE PULLEYS: Split steel

SPINDLES: Cast-iron roller bearing spindles - 1" shaft has an 8" 6-bolt flange design; Greasable (61")/Cast aluminum with 2.5" x 1" dual ball bearings, top access grease fittings with weep holes (52")

BLADES: 0.25" thick, heat-treated, Marbain

FRAME: 1.5" by 2" 11-gauge rectangular tubing

DECK MOUNTING: All four corners to be suspension mounted

HOURLY METER: Standard, activates with PTO

SEAT: Premium adjustable seat with optional seat insert

PAINT: Polyester powder coat paint. TGIC

NOISE PACKAGE: Noise damping engine shroud absorbs and reduces noises for improved operator and bystander comfort

WARRANTY: **Riding Mower:** 4 years (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months)
Belts, Tires, Brake Pads, Hoses, Battery, Blades: 90 days
Engine: See Manufacturer's Warranty

ROPS: Standard, folding roll-over protection with retractable seatbelt

* All power levels are stated gross horsepower per SAE J1940 as rated Briggs & Stratton.

** All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki.

^ Power levels rated by engine manufacturer.

Not all models available in California. Models subject to change.