



Go The Extra Yard.™



MODEL: IS® 500Z

SPECIFICATIONS: Dated 9-1-2011

TYPE:	Mid mount, zero turn, twin stick steering rider with suspension	DECK:	52" & 61" : iCD™ Cutting System 44" : Floating, 10 gauge with lap welded corners, plug welded second top deck, full spindle width and metal deck shields
DECK SIZE:	44", 52", 61"	DISCHARGE CHUTE:	Flexible rubber
ENGINE:	24 & 27 gross HP* Briggs & Stratton Professional Series, pressure lubrication, spin on oil filter, remote air cleaner	BELTS:	Drive system - heavy-duty B-section belt to both pumps Deck drive - one continuous loop B-section belt for spindles and deck drive
SUSPENSION:	Four-wheel suspension with pivoting front axle, spring assemblies and rear-wheel coil-over-shock suspension	SPINDLE PULLEYS:	Split Steel
FUEL TANKS:	Single, 5.5 gallon capacity 3.5" cap. Integrated cup holder	SPINDLES:	Cast aluminum with 2.5" x 1" dual ball bearings, top access grease fittings with weep holes
DRIVE SYSTEM:	Twin independent wheel motors and pumps, fans on 61" model, five bolt wheel hubs, with 1/2 qt. spin on oil filter and reservoir mounted inside the frame	BLADES:	0.25" thick, heat-treated, Marbain
SPEED:	0 - 8 MPH forward 0 - 4 MPH reverse	FRAME:	1.5" by 2" 11-gauge rectangular tubing
CONTROL SYSTEM:	Twin fold over stick type, adjustable steering	HOOR METER:	Standard, activated with PTO
PARKING BRAKE:	Drum Style	SEAT:	Adjustable, fore and aft, with optional fold down arm rests
BLADE ENGAGEMENT:	Electric clutch	PAINT:	Polyester powder coat paint; TGIC
HEIGHT CONTROL:	Foot activated, 0.25" increments, single pin adjust from 1.5" to 5"	WARRANTY:	Two (2) year commercial warranty, parts and labor. (90 days on belts, blades, tires and brake pads) Briggs engine (2) year manufacturer's warranty - consumer use (1) year manufacturer's warranty - commercial use
TIRES:	Drive: 20 x 8 x 10, 4 ply (44") 20 x 10 x 10, 4 ply (52" & 61") Caster - 11 X 4 x 5, 4 ply, tubeless, pneumatic	ROPS:	Standard, roll-over protection with retractable seatbelt

*All power levels are stated gross horsepower per SAE J1940 as rated Briggs & Stratton. **All power levels are stated gross horsepower per SAE J2723 as rated by Kawasaki. ^Power levels rated by engine manufacturer. Not all models available in California. Models subject to change.